



## Piedino di Livellamento in PE con perno Girevole

### Levelling Foot with Threaded Adjustable Bolt

Cod.	A	M	B	H	Carico max Statico Max Load daN	U.V.
A3EC30/0820	30	08MA	20	16	400	24
A3EC30/0840	30	08MA	40	16	400	24
A3EC30/0870	30	08MA	70	16	400	24
A3EC30/1040	30	10MA	40	18	500	24
A3EC40/0830	38	08MA	30	16	400	24
A3EC40/0850	38	08MA	50	16	400	24
A3EC40/1040	38	10MA	40	18	500	24
A3EC40/1060	38	10MA	60	18	500	24
A3EC40/10100	38	10MA	100	18	500	24
A3EC50/1050	48	10MA	50	18	500	24
A3EC50/10100	48	10MA	100	19	500	24
A3EC50/1240	48	12MA	40	19	600	24
A3EC50/1260	48	12MA	60	19	600	24
A3EC55/12100	55	12MA	100	19	600	24

#### Caratteristiche

**Materiale Base:** Polipropilene (PP)

**Materiale Stelo:** Acciaio Zincato

**Tipo Stelo:** Girevole

**Corredo Stelo:** Dado esagonale

**Presentazione Prodotto:**

Stelo fornito assemblato alla base

#### Product specification

**Base Material:** Polypropylene (PP)

**Stud Material:** Zinc Plated Steel

**Stud Type:** Revolving

**Spindle Outfit:** Hex nut

**Delivered:** Stud supplied applied to the base

