

“Speedy” Line EGL - EGLX

Chiusure a Leva speciali

Special Toggle Latches

Cod.	Cod. Inox	A	b	B	C	D	E	F	G	H	I	K	L	M	N	O	P	Q	R	S	T	Diam. Ø	Carico Max Max Load daN
2S.E1GL	2S.E1GLX	117,5	18	25	8,3	51-58	25	29	13	17,5	20	6,5	52,5	24	13,3	1,5	22-29	4,2	5,5	19	M5	5	100
2S.E2GL	2S.E2GLX	155,5	25	33	10	64-75	30,8	42	15	24	6	8	65	32	16,4	2	28-39	5,2	10	26	M6	6	200
2S.E3GL	2S.E3GLX	189,5	32	41,5	12,7	79,5-92	35,8	52	20	29,5	30	11	81,5	38	20,7	2,5	33-45,5	6,5	12,5	31	M8	8	300

EGL Caratteristiche

Materiale: Zincata, con molla di sicurezza

Presentazione Prodotto:

La chiusura è sempre fornita completa di staffetta di riscontro

Caratteristiche Specifiche:

Lucchettabile

EGLX Caratteristiche

Materiale: Acciaio inox AISI 304, con molla di sicurezza

Presentazione Prodotto:

La chiusura è sempre fornita completa di staffetta di riscontro

Caratteristiche Specifiche:

Lucchettabile

EGL Product specification

Material: Zinc plated, with safety spring

Product Presentation:

The toggle latch is always supplied with the strike

Specific Features:

Lockable

EGLX Product specification

Material: AISI 304 Stainless Steel, with safety spring

Product Presentation:

The toggle latch is always supplied with the strike

Specific Features:

Lockable

