

# SC/D

## Supporto Antivibrante a Campana con Dado

### Bell Mount with Threaded Nut

Cod.	M	C	B	G	H	F	E	S	Durezza Hardness Shore A	Carico max Statico Max Load daN
A2SC60/10	10MA	62	50	85	100	10	30	2	60	192
A2SC60/12	12MA	62	50	85	100	10	30	2	60	192
A2SC90/12	12MA	92	72	110	130	10	44	3	60	380
A2SC90/14	14MA	92	72	110	130	10	44	3	60	380
A2SC90/16	16MA	92	72	110	130	10	44	3	60	380
A2SC120/16	16MA	119	95	160	190	16	49	4	60	787
A2SC120/24	24MA	119	95	160	190	16	49	4	60	787
A2SC60/10-45	10MA	62	50	85	100	10	30	2	45	120
A2SC60/12-45	12MA	62	50	85	100	10	30	2	45	120
A2SC90/12-45	12MA	92	72	110	130	10	44	3	45	266
A2SC90/14-45	14MA	92	72	110	130	10	44	3	45	266

#### Caratteristiche

##### Versione supporto:

Con dado filettato saldato

**Materiale corpo:** Miscela gomma NR/SBR

**Tolleranza sulla durezza:** +/- 5 SH

**Parte metallica e/o fissaggio:**

Lamiera acciaio zincata

#### Product specification

**Version:** With welded threaded nut

**Main part material:**

NR/SBR rubber compound

**Hardness tolerance:** +/- 5 SH

**Metallic part:** Zinc plated steel sheet

